

## DECLARATION OF PERFORMANCE

### No. LE S355J2H


1. *Unique identification code of the product type:*  
**Seamless steel pipe according to EN 10210-1:2006, Grade S 355 J2H**
  
2. *Type, batch or serial no. or any element allowing identification of the construction product as required pursuant to Article 11(4):*  
**Heat number on pipe or on attached 3.1 mill test certificate**
  
3. *Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:*  
**Use in metallic structures or in composite metal and concrete structures**
  
4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required acc. to Article 11(5):*  
**voestalpine Tubulars GmbH & Co KG**  
**Alpinestraße 17, 8652 Kindberg-Aumühl**
  
5. *Where applicable, name and contact address of the authorized representative whose mandate covers the tasks acc. to Article 12(2):*  
**Not relevant**
  
6. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*  
**2+**
  
7. *In case of the declaration of performance concerning a construction product covered by a harmonized standard:*  
**The Notified Body– TÜV SÜD Industrie Service GmbH, Westendstr. 199, D – 80686 Munich, no. 0036 – has performed the initial inspection of the manufacturing plant and of factory production control as well as the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of the factory production control with no. 0036 – CPR – M - 070 – 2013.**
  
8. *In case of the declaration of performance concerning a construction product for which an European Technical Assessment has been issued:*  
**Not relevant**
  
9. *Declared performance:*

Essential characteristics (EN 10210-1:2006, Anhang ZA)	Performance	Harmonized technical specification
Tolerances on dimensions	passed	EN 10210-1:2006 EN 10210-2:2006
Elongation	≥ 22 % (for t≤40mm)	EN 10210-1:2006
Tensile strength	470 – 630 MPa (for t>3≤100mm)	EN 10210-1:2006
Yield strength	≥ 355 MPa (for t≤16mm) ≥ 345 MPa (for t>16≤40mm)	EN 10210-1:2006
Impact strength	≥ 27 J (-20°C)	EN 10210-1:2006
Weldability	passed: CEV < 0,45 (for t≤16mm) CEV < 0,47 (for t>16≤40mm)	EN 10210-1:2006
Durability	Performance not determined	EN 10210-1:2006

10. *The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.*

Signed for and on behalf of the manufacturer by:

Wolfgang Rainer, Managing Director

  
 .....  
 (signature)

Kindberg, October 30th, 2013

Robert Phillip, Managing Director

  
 .....  
 (signature)