

RÜCKZUGSKRÄFTE KS-OT | STANDARD & VERSTÄRKT

RETRACTION FORCE KS-OT | STANDARD & ENHANCED

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE	VERSTÄRKT ENHANCED	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]	[ID-NR.]	[kN]
KS-OT-060-00°	25100	1,1	23700	2,9
KS-OT-060-05°	25101	1,1	23701	2,9
KS-OT-060-10°	25102	1,3	23702	3,3
KS-OT-060-15°	25103	1,3	23703	3,3
KS-OT-060-20°	25104	1,5	23704	3,3
KS-OT-060-25°	25105	1,5	23705	3,8
KS-OT-060-30°	25106	1,4	23706	3,8
KS-OT-060-35°	25107	1,7	23707	4,5
KS-OT-060-40°	25108	1,7	23708	4,2
KS-OT-060-45°	25109	2,1	23709	5,5
KS-OT-060-50°	25110	2,1	23710	5,5
KS-OT-060-55°	25111	2,8	23711	5,6
KS-OT-060-60°	25112	2,8	23712	5,6
KS-OT-060-65°	25113	4,2	23713	5,7
KS-OT-060-70°	25114	5,7	23714	6
KS-OT-060-75°	25115	5,4	23715	5,8

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE	VERSTÄRKT ENHANCED	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]	[ID-NR.]	[kN]
KS-OT-085-00°	23415	1,2	23717	5,9
KS-OT-085-05°	23416	1,2	23718	5,9
KS-OT-085-10°	23417	1,3	23719	6,6
KS-OT-085-15°	23418	1,3	23720	6,6
KS-OT-085-20°	23419	1,3	23721	6,6
KS-OT-085-25°	23420	1,5	23722	7,5
KS-OT-085-30°	23421	1,8	23723	7,6
KS-OT-085-35°	23422	1,8	23724	7,6
KS-OT-085-40°	23423	1,7	23725	7,6
KS-OT-085-45°	23424	2,1	23726	9,7
KS-OT-085-50°	23425	2,1	23727	9,7
KS-OT-085-55°	23426	2,8	23728	10
KS-OT-085-60°	23427	2,8	23729	10
KS-OT-085-65°	23428	4,2	23730	11,1
KS-OT-085-70°	23429	4,1	23731	11,1
KS-OT-085-75°	23430	8	23732	12,2

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE	VERSTÄRKT ENHANCED	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]	[ID-NR.]	[kN]
KS-OT-110-00°	23430	2,7	23734	6
KS-OT-110-05°	23431	2,7	23735	6
KS-OT-110-10°	23432	3	23736	6,7
KS-OT-110-15°	23433	3	23737	6,7
KS-OT-110-20°	23434	3	23738	6,7
KS-OT-110-25°	23435	3,4	23739	7,5
KS-OT-110-30°	23436	3,4	23740	7,5
KS-OT-110-35°	23437	4	23741	8,7
KS-OT-110-40°	23438	4	23742	8,7
KS-OT-110-45°	23439	5	23743	10
KS-OT-110-50°	23440	4,7	23744	9,8
KS-OT-110-55°	23441	5,3	23745	11,2
KS-OT-110-60°	23442	6,1	23746	11,8
KS-OT-110-65°	23443	9,1	23747	12,2
KS-OT-110-70°	23444	11,4	23748	12,2
KS-OT-110-75°	23397	11,5	23749	12,2

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE	VERSTÄRKT ENHANCED	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]	[ID-NR.]	[kN]
KS-OT-150-00°	23445	4,2	23751	10
KS-OT-150-05°	23446	4,2	23752	10
KS-OT-150-10°	23447	4,7	23753	11,2
KS-OT-150-15°	23448	4,7	23754	11,2
KS-OT-150-20°	23449	4,7	23755	11,2
KS-OT-150-25°	23450	5,4	23756	12,9
KS-OT-150-30°	23451	5,3	23757	12,9
KS-OT-150-35°	23452	6,3	23758	14,6
KS-OT-150-40°	23453	6,3	23759	14,6
KS-OT-150-45°	23454	7,7	23760	18,8
KS-OT-150-50°	23455	7,7	23761	18,8
KS-OT-150-55°	23456	10,2	23762	19
KS-OT-150-60°	23457	10,1	23763	19
KS-OT-150-65°	23458	14,6	23764	19
KS-OT-150-70°	23459	16,9	23765	19
KS-OT-150-75°	23396	16,9	23766	19

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE	VERSTÄRKT ENHANCED	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]	[ID-NR.]	[kN]
KS-OT-180-00°	23460	4,2	23768	9,9
KS-OT-180-05°	23461	4,2	23769	10
KS-OT-180-10°	23462	4,8	23770	10,9
KS-OT-180-15°	23463	4,7	23771	10,9
KS-OT-180-20°	23464	4,7	23772	10,9
KS-OT-180-25°	23465	5,4	23773	13
KS-OT-180-30°	23466	5,4	23774	12,9
KS-OT-180-35°	23467	6,4	23775	15,3
KS-OT-180-40°	23468	6,3	23776	15,2
KS-OT-180-45°	23469	7,8	23777	18,8
KS-OT-180-50°	23470	7,7	23778	18,8
KS-OT-180-55°	23471	10,3	23779	19
KS-OT-180-60°	23472	10,2	23780	19
KS-OT-180-65°	23473	14,7	23781	19
KS-OT-180-70°	23474	16,6	23782	19
KS-OT-180-75°	23395	16,6	23783	19

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]
KS-OT-220-00°	23475	11,1
KS-OT-220-05°	23476	11,1
KS-OT-220-10°	23477	12,5
KS-OT-220-15°	23478	12,5
KS-OT-220-20°	23479	12,4
KS-OT-220-25°	23480	14,2
KS-OT-220-30°	23481	14,2
KS-OT-220-35°	23482	16,8
KS-OT-220-40°	23483	16,8
KS-OT-220-45°	23484	20,7
KS-OT-220-50°	23485	20,7
KS-OT-220-55°	23486	27,3
KS-OT-220-60°	23487	27,2
KS-OT-220-65°	23488	40,7
KS-OT-220-70°	23489	39,8
KS-OT-220-75°	23394	44

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]
KS-OT-260-00°	23490	22,1
KS-OT-260-05°	23491	22,1
KS-OT-260-10°	23492	24,8
KS-OT-260-15°	23493	24,7
KS-OT-260-20°	23494	24,7
KS-OT-260-25°	23495	28,3
KS-OT-260-30°	23496	28,2
KS-OT-260-35°	23497	33,4
KS-OT-260-40°	23498	33,4
KS-OT-260-45°	23499	41,3
KS-OT-260-50°	23500	41,2
KS-OT-260-55°	23501	44
KS-OT-260-60°	23502	44
KS-OT-260-65°	23503	44
KS-OT-260-70°	23504	44
KS-OT-260-75°	23393	44

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]
KS-OT-330-00°	23505	45,4
KS-OT-330-05°	23506	45,4
KS-OT-330-10°	23507	50,8
KS-OT-330-15°	23508	50,8
KS-OT-330-20°	23509	50,7
KS-OT-330-25°	23510	58,1
KS-OT-330-30°	23511	58
KS-OT-330-35°	23512	60
KS-OT-330-40°	23513	60
KS-OT-330-45°	23514	60
KS-OT-330-50°	23515	60
KS-OT-330-55°	23516	60
KS-OT-330-60°	23517	60
KS-OT-330-65°	23518	60
KS-OT-330-70°	23519	60
KS-OT-330-75°	23392	60

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]
KS-OT-400-00°	23520	45,6
KS-OT-400-05°	23521	45,5
KS-OT-400-10°	23522	51
KS-OT-400-15°	23523	50,9
KS-OT-400-20°	23524	50,8
KS-OT-400-25°	23525	58,2
KS-OT-400-30°	23526	58,1
KS-OT-400-35°	23527	60
KS-OT-400-40°	23528	60
KS-OT-400-45°	23529	60
KS-OT-400-50°	23530	60
KS-OT-400-55°	23531	60
KS-OT-400-60°	23532	60
KS-OT-400-65°	23533	60
KS-OT-400-70°	23534	60
KS-OT-400-75°	23535	60

SCHIEBER CAM UNIT	STANDARD STANDARD	RÜCKZUGSKRAFT RETRACTION FORCE
	[ID-NR.]	[kN]
KS-OT-500-00°	23537	60
KS-OT-500-05°	23538	60
KS-OT-500-10°	23539	60
KS-OT-500-15°	23540	60
KS-OT-500-20°	23541	60
KS-OT-500-25°	23542	60
KS-OT-500-30°	23543	60
KS-OT-500-35°	23544	60
KS-OT-500-40°	23545	60
KS-OT-500-45°	23546	60
KS-OT-500-50°	23547	60
KS-OT-500-55°	23548	60
KS-OT-500-60°	23549	60
KS-OT-500-65°	23550	60
KS-OT-500-70°	23551	60
KS-OT-500-75°	23552	60