



Landesgesellschaft
Österreich

Certificate of constancy of performance Certificate - No.: 0531 – CPR – 1317 – 1077

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Kremsbarrier 2 MH2C for pile driving ground condition

Containment level:	H2
Normalized working width:	W5
Impact severity:	A
Normalized dynamic deflection:	1,0 m
Normalized vehicle intrusion:	VI8
Resistance to snow removal:	Class 4
Durability: Steel, hot dip galvanized in accordance with EN ISO 1461	

placed on the market by

voestalpine Krems Finaltechnik GmbH

Schmidhüttenstrasse 5
3500 Krems, Austria

and produced in the manufacturing plant

voestalpine Krems Finaltechnik GmbH

Schmidhüttenstrasse 5
3500 Krems, Austria

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 1317-5:2007+A2:2012/AC:2012

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 18.11.2013, based on the report 24284/15.11.2013 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Wien, 06.10.2021



voestalpine
ONE STEP AHEAD.



Landesgesellschaft
Österreich

**Annex to certificate of constancy
of performance**
Certificate - No.: 0531 – CPR – 1317 – 1077

For the construction product **Kremsbarrier 2 MH2C for
pile driving ground
condition**

**Placed on the market
by** **voestalpine
Krems Finaltechnik GmbH
Schmidhüttenstraße 5
3500 Krems, AT**

Modification 1:
Approved on
12.12.2014

Side reinforcement:

The safety barrier may be installed without the outer side reinforcement plates (drawing no. 30-001.0995). The assessment and approval of this change is documented in modification report 28190, 12.12.2014.

Modification 2:
Approved on
18.12.2019

Glare protection:

A support structure for glare protection slats can be attached to the safety barrier. The assessment and approval of this change is documented in modification report 24405 Rev. 2, 18.12.2019.

Modification 3:
Approved on
06.10.2021

Handrail:

A handrail can be attached to the safety barrier. The assessment and approval of this change is documented in modification report 725185414, 06.09.2021.

Wien, 06.10.2021



(Dipl. – Ing. Gerald Bachler)

voestalpine
ONE STEP AHEAD.