1317 A2 englisch 21.03,2018

Ë

consistency of performance

certificate of

07.Str.071





Certificate of constancy of performance Certificate - No.: 0531 - CPR - 1317 - 2231

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

KREMSBARRIER 2 RH2C 1,27m for pile driving ground condition

Containment level: Normalized working width: W5 Impact severity: 1.2 m Normalized dynamic deflection: Normalized vehicle intrusion: VI7 Resistance to snow removal: Class 4

durability: galvanized in accordance with EN ISO 1461

produced by

voestalpine Krems Finaltechnik GmbH Schmidhüttenstrasse 5 Postfach 42 **A-3500 Krems**

and produced in the manufacturing plant voestalpine Krems Finaltechnik GmbH Schmidhüttenstrasse 5 Postfach 42 **A-3500 Krems**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA 1.b of the standard

EN 1317-5:2007+A2:2012/AC:2012

under system 1 for the performances set out above are applied and that the construction product fulfils all the prescribed requirements for these performances.

This certificate was first issued on 10.04.2018, based on the report 93474_2/10.04.2018 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performances of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body.

Notified body, No. 0531

Wien, 12.12.2019

voestalpine

Ing. Gerald Bachler)

TÜV[®]

EN 1317 A2 englisch 21.03,2018

07.Str.071 certificate of consistency of performance





Annex to certificate of constancy of performance

Certificate - No.: 0531 - CPR - 1317 - 2231

For the construction product Kremsbarrier 2 RH2C

1,27m for pile driving ground conditions

Placed on the market by

voestalpine Krems Finaltechnik GmbH Schmidhüttenstraße 5 A – 3500 Krems

Modification 1:

Approved on 20.11.2013

Handrail:

The VRS may be extended by a handrail. No additional drilling on the system must be performed. The functionality remains. The detailed function of the handrail is described in the technical report that is part of the modification report. The modification was assessed in the report 21628_Rev2. The results of the report may be used for this product as well.

Wien, 12.12.2019



