



Organic-coated steel strip

colofer® HOME SILVER data sheet | Page 1/2 | 10/2023

colofer® HOME SILVER

Diversity in glittering silver

Trendy and timeless are not contradictory terms!

colofer® HOME SILVER provides a highly modern design and elegant appearance. With a nearly inexhaustible selection of various silver shades, colofer® HOME SILVER makes it possible to meet the most individual customer requirements.

Convincing advantages:

- » Standard and metallic silver color tones
- » Numerous color nuances
- » Smaller lot sizes possible

Typical applications:

- » Washing machines
- » Refrigerators
- » Dryers
- » Dishwashers



Premium quality with reduced carbon footprint





Our colofer® technical support consists of a large pool of experts who will be happy to assist you with all your inquiries.





| Properties | Testing standard/Inspection requirement | Typical values |
|---|---|---|
| Coating thickness | EN 13523-1 | > 21 μm |
| Colors 1) | ISO 3668 EN 13523-3 | upon request |
| Surface appearance | - | upon request, smooth or structured |
| Gloss (60°) | EN 13523-2 | upon request |
| Adhesion (cross cut) | ISO 2409 | 0 2) |
| Adhesion after bending | EN 13523-7 | ≤ 0,5 T ²⁾ |
| Crack formation after bending | EN 13523-7 | <u>≤2T</u> |
| Scratch resistance | based on EN 13523-12 | > 15 N |
| Resistance to solvents | EN 13523-11 | ≥ 50 DH |
| Resistance to rapid deformation (Impact test) | EN 13523-5 | ≥ 18 J |
| Corrosion resistance » Salt spray test | EN 13523-8 | Test duration: 240 h No formation of blisters on surface |
| Resistance to humidity » Continuous humidity test | EN 13523-25 | Test duration: 500 h No formation of blisters on surface |
| Recommended processing temperature | - | 20-40 °C |
| Environmental impact | - | RoHS-compliant |

¹⁾ Color tolerance from one production lot to the next cannot be guaranteed for metallic surfaces.



Premium quality with reduced carbon footprint



greentec steel

Organic-coated steel strip – greentec steel Edition

Max. carbon footprint 2.23 kg $\rm CO_2 e$ per kg of steel $^{1)}$

All products, dimensions and steel grades listed in each voestalpine supply range are available as greentec steel Edition.

All values reflect the current status of our experience and knowledge. Slight deviations may occur as a result of specific color and sheet thickness. Paper printouts cannot be updated on a regular basis. For this reason, please refer to the most recent version of the online data sheets found on our home page. Technical changes reserved, errors and misprints excepted. No part of this publication may be reprinted without explicit written permission by voestalpine Stahl GmbH.

To find out more about colofer®, visit us on our website at www.voestalpine.com/colofer



²⁾ Dependent on coating type and sheet thickness

 $^{^{\}mbox{\tiny 1)}}\,\mbox{per}\,\mbox{EN}\,\mbox{15804+A2}$ (EPD methodology) cradle to gate